

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

920190-95750

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

IN THE APPLICATION OF	)	
	)	
Michael John Sargeant	)	
	)	
SERIAL NO: To Be Assigned	)	Customer number: 23644
	)	
FILED: Herewith	)	
	)	
FOR: Cabinet for Electronic Equipment	)	

**CLAIM FOR PRIORITY**


Honorable Director of Patents and Trademarks  
P.O. Box 1450  
Alexandria, VA 22313-1450

Dear Sir:

Under the International Convention, for the purposes of priority, applicant claims the benefit of United Kingdom Application No. 0309722.7, filed 29 April 2003.

A certified copy of said application will is submitted herewith.

March 31, 2004

Respectfully submitted,  
  
William M. Lee, Jr.  
Registration No. 26,935  
Barnes & Thornburg  
P.O. Box 2786  
Chicago, Illinois 60690-2786  
(312) 214-4800  
(312) 759-5646 (fax)



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *Andrew Gensy*  
Dated 16 February 2004

## **Cabinet for electronic equipment**

This invention relates to cabinets for electronic equipment. The invention is particularly, although not exclusively, concerned with cabinets for computer equipment such as servers.

One object of the invention is to provide a novel form of cabinet construction, which is intrinsically strong and resistant to shock and vibration.

### *Summary of the invention*

According to the invention, a metal cabinet for housing electronic equipment comprises:

- front and rear frames, each comprising a welded rectangular frame;
- a pair of top struts fastened between the front and rear frames at the top;
- a base panel fastened between the front and rear frames at the bottom;
- a pair of rectangular side panels fastened between the front and rear frames at the sides;
- a top cover, fastened to the tops of the front and rear frames and to the top struts; and
- a rear cover, fastened to the rear frame.

A cabinet constructed in accordance with the invention has a number of advantages. One advantage is that, because the front and rear frames are welded rather than bolted together as in conventional constructions, the cabinet is more rigid and resistant to shock and vibration.

Preferably, the side panels are flush with the edges of the front and rear frames, rather than covering the whole of the side of the cabinet. An advantage of this is that it means that

the width of the side panels is less than the overall back-to-front depth of the cabinet. This is useful where the parts of the cabinet have to be manoeuvred through small openings during installation.

#### *Brief Description of the Drawings*

One cabinet in accordance with the invention will now be described by way of example with reference to the accompanying drawings.

Figure 1 shows parts of the cabinet before assembly.

Figures 2 and 3 show two successive stages in the construction of the cabinet.

#### *Description of an embodiment of the invention*

In this example, the cabinet is approximately 1800mm high, 600mm wide, and 850mm deep, and is intended to house a number of conventional rack-mounted computer modules.

Figure 1 shows the main parts of the cabinet, before assembly, as follows:

- Front and rear frames 10, 11.
- Top stays 12, 13.
- Base panel 14.
- Side panels 15, 16.
- Top cover 17.
- Rear cover 18.

The front and rear frames 10, 11 are each constructed from four elongated steel sections, welded together to form a rigid rectangular frame.

The cabinet is assembled as follows.

First, the front and rear frames 10, 11 are stood on end, and the top stays 12, 13 are fitted, linking the tops of the frames, using eight M6 X 16 cap head screws with plain and spring washers. The base panel 14 is then fastened to the bottoms of the frames, using eight M6 X 10 cap head screws with plain and spring washers.

Figure 2 shows the cabinet at this stage of assembly, viewed from the rear right hand corner.

Next, the side panels 15, 16 are fitted between the front and rear frames using M6 X 10 countersunk screws. The top cover 17 is fitted to the tops of the front and rear frames and the top stays, using M6 X 16 cap head screws with plain and spring washers. Rear cover 18 is similarly fitted to the rear frame.

Figure 3 shows the cabinet after these steps. The cabinet is now ready to receive any required fittings (not shown), such as power cables, patch panels, and so on.

It can be seen that each side panel is flush with the ends of the front and rear frames. As a result, the width of each side panel is less than the overall back-to-front depth of the cabinet. In this case, the side panels are 630mm wide, compared with the overall cabinet depth of 850mm. This is useful where the parts of the cabinet have to be manoeuvred through small openings during installation.

It can be also be seen that, because the front and rear frames are welded rather than bolted together as in conventional constructions, the cabinet is more rigid and resistant to shock and vibration.

*Some possible modifications*

It will be appreciated that many modifications may be made to the system described above without departing from the scope of the present invention. For example, the cabinet may be of a different shape or size from that specified, and may be designed to house different types of equipment.

## CLAIMS

1. A metal cabinet for housing electronic equipment, the cabinet comprising:

- front and rear frames, each comprising a welded rectangular frame;
- a pair of top struts fastened between the front and rear frames at the top;
- a base panel fastened between the front and rear frames at the bottom;
- a pair of rectangular side panels fastened between the front and rear frames at the sides;
- a top cover, fastened to the tops of the front and rear frames and to the top struts; and
- a rear cover, fastened to the rear frame.

2. A cabinet according to claim 1 wherein the side panels are flush with the edges of the front and rear frames.

3. A metal cabinet for housing electronic equipment, substantially as hereinbefore described with reference to the accompanying drawings.

4. A method of constructing a cabinet for housing electronic equipment, comprising the steps:

- forming front and rear frames, each comprising a welded rectangular frame;
- fastening a pair of top struts between the front and rear frames at the top;
- fastening a base panel between the front and rear frames at the bottom;
- fastening pair of rectangular side panels between the front and rear frames at the sides;



- fastening a top cover to the tops of the front and rear frames and to the top struts; and
- fastening a rear cover to the rear frame.

5. A method of constructing a cabinet for housing electronic equipment, substantially as hereinbefore described with reference to the accompanying drawings.

**ABSTRACT**

A metal cabinet for housing electronic equipment comprises front and rear frames, each comprising a welded rectangular frame. A pair of top struts are fastened between the front and rear frames at the top. A base panel is fastened between the front and rear frames at the bottom. A pair of rectangular side panels is fastened between the front and rear frames at the sides. A top cover is fastened to the tops of the front and rear frames and to the top struts. A rear cover is fastened to the rear frame.




FIG. 1

2/3




FIG. 2

3/3




FIG. 3